

Windsor® Starter Scotchgard™ Protector

Starter Shingles - Impact & Algae Resistant

Required for Windsor* installation, Windsor* Starter shingles are designed to fortify the first course of shingles most prone to wind uplift, shingle blow-off, and moisture migration. Windsor® Starter shingles are made with our industry-leading NEX® Polymer Modified (Rubberized) Asphalt, an innovative technology that uses rubber polymers (molecular compounds) to strengthen and rubberize the asphalt core of the shingle for vastly superior all-weather resilience and longevity.

It's more sustainable too. Added to the mix are upcycled polymers from used tires and plastic bags. Sustainability without sacrificing performance.

NEX® RUBBERIZED ASPHALT


Asphalt core of shingle is rubberized with synthetic rubber polymers (SBS) to enhance shingle strength, flexibility, and resilience. Class 4 impact rating.

UPCYCLED RUBBER & PLASTIC

plastic improve shingle durability while diverting used tires and plastic bags from the landfill.

Polymers from recycled rubber and

Provides structural reinforcement and tear strength.



3M™ ROOFING GRANULES

Ceramic-coated granules protect shingle from weather and UV aging. Superior granule adhesion.

3M™ COPPER GRANULES

Reduce black streaks caused by algae growth. Limited Lifetime algae warranty.

3M™ SMOG-REDUCING GRANULES

FIBERGLASS MAT


Clean the air of emission pollutants with a smoq-fighting roof.1

INSTALLED THIRD

When installing a complete 5-component system, starter shingles are installed third, after the underlayment, and prior to the field (roofing) shingles. Correct installation of Windsor® shingles requires the use of 2 starter shingle products: Smart Start™ starter shingles followed by Windsor® Starter shingles.

COLOR MATCH

Windsor® Starter shingles match Windsor® shingle colors.



See shingle colors on a roof, or your roof, at www.malarkeyroofing.com/ roof-designer.

Scotchgard and Scotchgard Protector, including the 3M logo, are all trademarks of 3M.

This version supersedes all previous versions. Rev. 06/22





Source: Lawrence Berkeley National Laboratory and 3M. Test Compliance - ASTM D3462 and UL 2218 Class 4.

⁺ For complete information on all warranties, please reference Malarkey's Shingle and Accessory Warranty available at www.malarkeyroofing.com/warranties.